

1 :

0000 000 00 .000 00000 0000000 0000 00000 0 00 00000 0000 00 0000000 000 000 0000 0000 0000000 0 000000
00 0000 00 0000 0 00000000 00000000 0000 0000000 0000000 0000 00 0000 0000000 00 0000000 00 000000 0000000
0000 0 0000 00 0000 000 0000 000000 00 00000 .00000 0000 00 0000 00000 0000 0 00000 00 0000 000 0000
0000 00000000 000000 00 000 000000 00 00 0000000 000 000 000 000 000000000 000 0000 00000 00 000 0000 0000000.



09120710200 □ □□□□□□□ □□□ □□□□ □□□□□□□□

[illegible]

09120710200



3 □□ □□□ □□□□ □□□□□□ □□□□ □□□□ □□ □□□□

0000 .0000 0000 000000 0 00000000 000 000000 0000 00 00000000 0000 00 0000 00 00000000 00000000 00 00 00000000
00000000 0000 00 .00000000 00 000 00000 00000000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
00 00000000 000000 00 000000 00 00 0000000000 0000 0000 000000000000 00 00000000:

- 

0000000 .00000 00000 0000000 0000000 000000 0000 000 000000 000000 00 00000 00 000 00 000000000 00000 00 00 0000
 000000 00 00000 0000000 000000 00000 ... 0 000000 0000 000 000000000 00000 00000000 000000 00 0000 00 00 000000 00 00000
 000000 00 00000000 0000 00000 0000 .00000 00000 00 00000 00 00000 00 000000000 00 00000 00000 0 00 00000000 00000 00000 00
 0000 00 0000000 0000 00 00 00000000 00000 .0000000 00 000000 0000 0000 00 0 00000 00000 0000000 0000 00000 000000 0000 00
 0000 00 0000 0000000 0 000000 00 00 0000 00000 00 0 0000 00000 0000000 0000 00000 000000 00000 00000 0000 00

- 

[illegible]

- 

1. 检查并清理管口：首先，检查待粘接的PVC管端口，确保其干净、无油污、无水分。如有必要，使用砂纸轻轻打磨管口，以去除表面的杂质和氧化层。

2. 涂抹胶水：将PVC胶水均匀地涂抹在管口的外表面。涂抹时，应使用刷子或专用的涂抹工具，确保胶水覆盖整个管口，并稍微溢出到管口边缘。

3. 插入管头：将待粘接的管头迅速插入已涂好胶水的管口。插入时，应施加一定的压力，使管头与管口紧密结合。

4. 固定与固化：插入后，保持管头在管口内一段时间，以确保胶水充分填充并固化。通常，PVC胶水的固化时间约为15-30分钟。在此期间，应避免对连接处施加外力或移动。

5. 检查密封性：固化完成后，检查连接处是否牢固，无泄漏现象。如有必要，可再次涂抹胶水进行加固。



1. 2. 3. 4. 5.

1. 2. 3. 4. 5.

1. 2. 3. 4. 5.
2. 3. 4. 5.
3. 4. 5.
4. 5.
- 5.



How to Fix a Clogged Sink Drain

There are many reasons why a sink drain might be clogged. The most common cause is a buildup of food particles, grease, and hair. Other causes include a blocked vent pipe or a problem with the main sewer line. To fix a clogged sink drain, you will need to identify the cause of the problem and then take the appropriate steps to clear the drain.

1. If the drain is clogged with food particles, grease, or hair, you can try using a plunger to clear the blockage. To use a plunger, place the cup over the drain and push and pull the handle several times. This can help to dislodge the clog and allow water to flow freely.

- [illegible]



1. 检查并更换损坏的密封垫圈或O型圈。

2. 如果管道本身有裂缝，可能需要更换受损部分。

[illegible]